

Compact & Reliable 24-Pin Narrow Carriage Flatbed Impact Printer with space-saving dimensions



DP550

Compact & Reliable 24-Pin
Narrow Carriage Flatbed Impact Printer

Highlights:

- Fast printing speed of up to 400 characters per second
- Better connectivity with Standard Parallel & USB 2.0 Interfaces, optional Serial and Ethernet Interfaces
- Optimum efficiency with 7-pay forms printout (Original + 6 Copies)
- Trustworthy printhead (500 million strokes)
- Choice of 9 built-in bar code formats for maximum versatility

DP550

Compact & Reliable 24-Pin Narrow Carriage Flatbed Impact Printer



Specification:

Print type	24-pin impact dot matrix
Print direction	Bi-directional with logic seeking
Print width	80 Columns (10CPI) / 203.2mm
Print speed	Super high speed 400 CPS High speed 300 CPS Normal 150 CPS
Print head	Diameter of wire: 0.22mm, Life: 500 million strokes/wire
Resolution	360×360 DPI (Maximum)
Character sets	17 international character sets U.S.A, France, Germany, U.K, Denmark1, Sweden, Italy, Spain1, Japan, Norway, Denmark2, Spain2, Latin Am, Korea, Legal, Netherlands, Turkey
Fonts	Draft, Roman, Sans Serif, Courier, Prestige, Script, OCR-A, OCR-B, Orator
Bar code	EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128 B, Code 128 C, NW-7
Character pitch	10CPI, 12CPI, 15CPI, proportional
Line space	1/6 inch, 1/8 inch, programmable in 1/360 inch increments
Emulation	EPSON ESC/PK2, OKI 5530SC
Interface	
Standard	Bi-directional parallel interface (IEEE-1284 nibble mode), USB 2.0 (Full-Speed) interface
Options	RS-232C serial interface or 10/100 Base-T Ethernet interface
Input Buffer	132KB
Ribbon	
Model	JMR118
Life	> 10 million characters (draft mode)
Noise	<55dB(A)(ISO7779 standard)
Paper feed type	
Cut sheet	front in, front out
Continuous paper	rear in, front out

Being compact, reliable and easy to use, Jolimark DP550 has been widely used in payment counters & retail stores, which has limited space and need high reliability.

Paper specification	
Cut sheet, card, postcard	Width: 65~260mm, Length: 55~536mm, Weight: 45~250 g/m ²
Continuous paper	Width: 76~260mm, Weight: Single sheet: 52~128 g/m ² , Multiple part: Every page 40~58 g/m ²
Max paper thickness	0.8mm
Copy	Original+6 copies
Automatic function	
Options	Automatic paper edge detection, Paper skew detection, Black mark detection
Compress set	Compressed printing for character and graphics
Special function	Automatic Pin Break Compensation, Automatic Pin Alternation, Automatic Emulation Match, Online Parameter Setting, LCD display
Dimension	378mm(W) × 322mm(D) × 209mm(H)
Weight	Approx. 6.4Kg
Environmental conditions	
Operating	Temperature: 5~40°C, Humidity: 40%RH~90%RH(No condensation)
Storage	Temperature: -40~55°C, Humidity: ≤93%RH(40°C, No condensation)
Power requirements	Rated voltage: 198~242V or 100~110V, Rated frequency range 50~60Hz
Safety marks	GB4943
Certificate	



DNVISO14001



BSIISO9001



OHSAS 18001

*The specifications above are subject to be changed without notice.

Jolimark®

Address: Unit 01, 23A/F, K.Wah Centre, 191 Java Road, North Point, Hong Kong
Tel: (852) 25582457 Fax: (852) 28979610
Email: sales@kongyue.com.hk Http://www.jolimark.com/en